

SONIC SIFTER SEPARATOR (L3P)



SPECIFICATIONS

Capacity 3" Acrylic

6 Acrylic L3-S Sieves

3 Acrylic L3-M (Precision Sieves)

Dimensions

10" w x 12" d x 23" h
(25 cm x 31 cm x 61 cm)

Weight

43 lbs. (20 kg) net

Operating Range

Temperatures 0° F to 120° F
(-18° C to 49° C)

Humidity non-condensing

Temperature and humidity should be controlled for optimal results

Timer

± 2 seconds over 24 hours

Agitation Method

Sonic Wave (top) and Vertical Mechanical Pulse (bottom)

RELIABLE. PRECISE. VERSATILE.

Tried and true for 50 years, the world's ORIGINAL Sonic Sifter Separator, otherwise known as the L3P, has become the industry standard and the go-to technology for precision research and quality assurance applications.

Producing results that are typically only achieved by wet sieving, this device uses specially designed 3" diameter clear sieves and an oscillating air column, created by a sonic wave, to separate fine particles. This technology dramatically shortens test times, is virtually maintenance free and produces consistent, accurate results.

FEATURES

- ✓ **Ideal for FINE particle separation** - Sieves range from 5.6 mm to 3 μ m
- ✓ **Simple to operate**
- ✓ **Clear acrylic framed sieves** allow for a visual reference to determine proper power level and finish point
- ✓ **Variable amplitude control** - Action can be manipulated to separate particles at maximum efficiency
- ✓ Little to **no screen wear or particle attrition**
- ✓ Large variety of special 3" acrylic sieves with **ASTM E11** wire cloth or **ASTM E161** precision electroformed mesh
- ✓ **On/off vertical mechanical pulse**
- ✓ Each unit **includes a complete Stack Assembly** comprised of: 1 Column Lock, 1 Diaphragm, 1 Top Cone, 6 Clear Acrylic Spacers, 1 Fines Collector and 1 Fines Collector Holder
- ✓ **One-year limited warranty**

SONIC SIFTER

L3P – 110vac/60Hz

L3P-15 – 110vac/50Hz

L3P-25 – 220vac/50Hz

L3P-26 – 220vac/60Hz

3" diameter acrylic sieves are sold separately.

L3-N8 – Horizontal Pulse Accessory (110vac/60Hz)

P6385 - Transformer for Horizontal Pulse Accessory in 220vac power environments



UPGRADE: Horizontal Pulse Accessory

A must for accurate separations below 45 μ m. This device helps eliminate agglomerates in extremely fine powders by tapping on alternating sides of the sieve stack while testing.

The ring occupies the lowest space within the stack assembly.